



Clear Coating over Tile Roof: 5-Year System

Materials Needed:

Product	Application Rate	Application Calculator
Roof & Tile Primer	0.5 gallons/SQ	0.5 x ___ SQs = ___ Gallons
Clear Roof & Tile Sealer	1.25 gallon/SQ	1.25 x ___ SQs = ___ Gallons

NOTE: 1 SQ = 100 sq. ft.

Always consult your Metacrylics® rep or contact Metacrylics for full system specifications.

General Application Guidelines

1. Thoroughly pressure wash roof.
2. Apply Metacrylics® Roof & Tile Primer @ 0.5 gallons/SQ to entire roof. Allow 1-4 hours to cure. Do not apply to damp surfaces or if moisture is imminent within 24 hours.
3. Apply Metacrylics® Clear Roof & Tile Sealer @ 0.75 gallons/SQ to the entire roof. Allow 4 hours to cure between coats. Do not apply to damp surfaces or if moisture is imminent within 24 hours as this will cause the sealer to turn cloudy & white until it dries.
4. Apply final Metacrylics® Clear Roof & Tile Sealer @ 0.75 gallons/SQ to the entire roof. Allow 24 hours to cure. Do not apply to damp surfaces or if moisture is imminent within 24 hours, as this will cause the sealer to turn cloudy & white until it dries.



Color Coating over Tile Roof: 5-Year System

Materials Needed:

Product	Application Rate	Application Calculator
Roof & Tile Primer	0.5 gallons/SQ	0.5 x ___ SQs = ___ Gallons
Color Roof & Tile Sealer	1.25 gallon/SQ	1.25 x ___ SQs = ___ Gallons

NOTE: 1 SQ = 100 sq. ft.

Always consult your Metacrylics[®] rep or contact Metacrylics for full system specifications.

General Application Guidelines

1. Thoroughly pressure wash roof.
2. Apply Metacrylics[®] Roof & Tile Primer @ 0.5 gallons/SQ to entire roof. Allow 1-4 hours to cure. Do not apply to damp surfaces or if moisture is imminent within 24 hours.
3. Apply Metacrylics[®] Color Roof & Tile Sealer @ 0.75 gallons/SQ to the entire roof. Allow 4 hours to cure between coats. Do not apply to damp surfaces or if moisture is imminent within 24 hours, as this will cause the sealer to turn cloudy & white until it dries.
4. Apply final Metacrylics[®] Color Roof & Tile Sealer @ 0.75 gallons/SQ to the entire roof. Allow 24 hours to cure. Do not apply to damp surfaces or if moisture is imminent within 24 hours, as this will cause the sealer to turn cloudy & white until it dries.



Color Coating over Tile Roof: 10-Year System

Materials Needed:

Product	Application Rate	Application Calculator
Roof & Tile Primer	0.5 gallons/SQ	0.5 x ___ SQs = ___ Gallons
Color Roof & Tile Sealer	1.25 gallon/SQ	1.25 x ___ SQs = ___ Gallons
Clear Roof & Tile Sealer	0.5 gallons/SQ	0.5 x ___ SQs = ___ Gallons

NOTE: 1 SQ = 100 sq. ft.

Always consult your Metacrylics[®] rep or contact Metacrylics for full system specifications.

General Application Guidelines

1. Thoroughly pressure wash roof.
2. Apply Metacrylics[®] Roof & Tile Primer @ 0.5 gallons/SQ to entire roof. Allow 1-4 hours to cure. Do not apply to damp surfaces or if moisture is imminent within 24 hours.
3. Apply Metacrylics[®] Color Roof & Tile Sealer @ 0.75 gallons/SQ to the entire roof. Allow 4-24 hours to cure between coats. Do not apply to damp surfaces or if moisture is imminent within 24 hours, as this will cause the sealer to turn cloudy & white until it dries..
4. Apply final Metacrylics[®] Color Roof & Tile Sealer @ 0.75 gallons/SQ to the entire roof. Allow 4-8 hours to cure. Do not apply to damp surfaces or if moisture is imminent within 24 hours, as this will cause the sealer to turn cloudy & white until it dries.
5. Apply Metacrylics[®] Clear Roof & Tile Sealer @ 0.5 gallons/SQ to the entire roof. Allow 24 hours to cure. Do not apply to damp surfaces or if moisture is imminent within 24 hours, as this will cause the sealer to turn cloudy & white until it dries.